

TECHNICAL DATASHEET

Code	D-Box-60-E
Brief Description	UN 4D/4DV Plywood box D-Box-60-E, mm 1180x780x780h inner useful
Type	D-Box-60-E
Print	Neutral
Provided	Flat - without vermiculite
Approval	4D/X352/S and 4DV/X229.6/S
In compliance with	ISPM15
Country of origin	Italy
Tare (box weight)	35,1 kg
Dimensions outer	1200 x 800 x 920 h mm
Dimensions inner	1180 x 780 x 780 h mm



For shipping:

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Closing
Nr. 48 glass bottles of 1 L each		352 (X352)	4D/X352/S and 4DV/X229.6/S	Don't require nails or straps
Solid products in PE bags inserted in one PE bag		352 (Y352)	4D/X352/S and 4DV/X229.6/S	Don't require nails or straps
Objects and inner packagings of all types	122,40	229,60 (X229.60)	D-Box-60 – 4DV/X229.6	Don't require nails or straps
Solid products in PE bags inserted in one PE bag		285,10 (X285.10)		Don't require nails or straps

Description

UN certified 4D and 4DV packagings (plywood boxes) suitable for the shipment of different objects and inner packagings as specified in the summary table. UN certified 4D plywood boxes can only be utilized with the specific packagings with which they have been tested. For the correct use of UN certified 4DV boxes it is necessary to follow the assembly instructions printed on every box. The correct preparation of these 4DV boxes provide that they be used in combination with one containment bag and Vermiculite (absorbent inert material).