

TECHNICAL DATASHEET

Code	4GV-86A-NT
Brief Description	UN 4GV box PGV86 assembled + Vermiculite, mm 280x280x260h inner useful
Type	PGV86
Print	Neutral
Provided	Assembled - 1 extra bag - with vermiculite
Approval	4GV/X14.5/S/** B/SERPAC.412-130035
Country of origin	Italy
Dimensions inner	330 x 330 x 310 h mm
Dimensions outer	340 x 340 x 340 h mm
Dimensions pallet	1560 x 800 x 1750 h mm
Weight of the fibreboard box	0,858 kg each
Package	Pack of 2 pieces


For shipping:

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Minimum distance of Vermiculite between containers, bottom and lid walls mm	Tape, width, system
Objects and inner packagings of all types	9,50	14,50 (X14.50)	PGV86-4GV/X14.8	25	PP36 , 50 mm
Lithium Battery with Vermiculite (P908, P909, P910)	9,50	14,50 (X14.50)	PGV86-4GV/X14.8	Da verificare*	PP36 , 50 mm

Description
UN certified 4GV fibreboard, assembled supplied, with 1 PE bag - PGV86.

UN certified 4GV packagings (UN certified 4GV fibreboard boxes) suitable for shipping objects or any kind of inner packagings containing solid or liquid substances of packing group I, II, III.

For a proper use of UN certified 4GV boxes, it is important to follow the instructions printed on the flap of each box.

The correct preparation of these UN certified 4GV boxes requires their use in combination with vermiculite (inert absorbent material).