

TECHNICAL DATASHEET

Code	4GV-82S-NT
Brief Description	UN 4GV box PGV82 flat + 2 bags, mm 390x290x360h inner
Type	PGV82
Print	Neutral
Provided	Flat - with 2 bags - without vermiculite
Approval	4GV/X14/S/** B/SERPAC.412-060036
Box type	Die-cut box
Country of origin	Italy
Dimensions inner	390 x 290 x 360 h mm
Dimensions outer	400 x 300 x 390 h mm
Dimensions package	1050 x 700 x 530 h mm
Dimensions pallet	1400 x 1150 x 1250 h mm
Weight of the fibreboard box	0,858 kg each
Package	Pack of 20 pieces



For shipping:

✓ ADR
 ✓ RID
 ✓ ADN
 ✓ IMDG
 ✓ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Minimum distance of Vermiculite between containers, bottom and lid walls mm	Tape, width, system
Objects and inner packagings of all types	8,50	14 (X14)	PGV82-4GV/X14	20	—
Lithium Battery with Vermiculite (P908, P909, P910)	8,50	14 (X14)	PGV82-4GV/X14	Da verificare*	—

Description

UN certified 4GV fibreboard, flat supplied, with PE bags - PGV82.

UN certified 4GV packagings (UN certified 4GV fibreboard boxes) suitable for shipping objects or any kind of inner packagings containing solid or liquid substances of packing group I, II, III.

UN certified 4GV boxes flat are supplied with 2 PE bags, except for PGV85 box which is supplied with only 1 PE bag.

For a proper use of UN certified 4GV boxes, it is important to follow the instructions printed on the flap of each box.

The correct preparation of these UN certified 4GV boxes requires their use in combination with vermiculite (inert absorbent material).