

## TECHNICAL DATASHEET

<b>Code</b>	4GV-85S-NT
<b>Brief Description</b>	UN 4GV box PGV85 flat + bag, mm 775x575x502h inner
<b>Type</b>	PGV85
<b>Print</b>	Neutral
<b>Provided</b>	Flat - with 1 bag - without vermiculite
<b>Approval</b>	4GV/X78/S/** B/SERPAC.412-060146
<b>Box type</b>	American
<b>Country of origin</b>	Italy
<b>Vibration test</b>	Yes (178.608 - 49CFR)
<b>Dimensions inner</b>	775 x 575 x 502 h mm
<b>Dimensions outer</b>	800 x 600 x 550 h mm
<b>Dimensions package</b>	1400 x 950 x 310 h mm
<b>Dimensions pallet</b>	1400 x 1000 x 1450 h mm
<b>Weight of the fibreboard box</b>	4,700 kg each
<b>Package</b>	Pack of 9 pieces


**For shipping:**

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Minimum distance of Vermiculite between containers, bottom and lid walls mm	Tape, width, system
Objects and inner packagings of all types	45,00	78 (X78)	PGV85-4GV/X78	60	<a href="#">RB</a> , 50 mm, <a href="#">U</a>
Lithium Battery with Vermiculite (P908, P909, P910)	45,00	78 (X78)	PGV85-4GV/X78		<a href="#">RB</a> , 50 mm, <a href="#">U</a>
Nr. 1 Lithium Battery with Grain (P908, P909, P910)	68,00	110 (110)	PG2024	Da verificare*	<a href="#">RB</a> , 50 mm, <a href="#">U</a>

**Description**
**UN certified 4GV fibreboard, flat supplied, with PE bags - PGV85.**

UN certified 4GV packagings (UN certified 4GV fibreboard boxes) suitable for shipping objects or any kind of inner packagings containing solid or liquid substances of packing group I, II, III.

UN certified 4GV boxes flat are supplied with 1 PE bag.

For a proper use of UN certified 4GV boxes, it is important to follow the instructions printed on the flap of each box.

The correct preparation of these UN certified 4GV boxes requires their use in combination with vermiculite (inert absorbent material)